



EM-T40

企业级手持机

- Capture data with 26-key keypad
- ARM octa-core processor, Support for Android 11 system
- WiFi /4G/BT5.0, multiple communication options
- Equipped with 4500mAh large capacity battery
- Supports 2D scanning, NFC, and other functional modules
- IP65 high protection level, in accordance with MIL-STD-810G



Durability	- MIL-STD-810G certified 26 drops from 4ft (each face, edge and corner) - IP65 certified
Operating System	Android 11 (GMS)
Processor	- MT6762 (4x 2.0Ghz Cortex-A53, 4x 1.5Ghz Cortex-A53)
Graphics	IMG GE8320 650MHz
Memory	4GB LPDDR4x on board
Storage	64GB Emmc 5.1
Display	4.0" FHD(480*800), 300nits sunlight readable display 5-point capacitive touchscreen
Audio	- Integrated microphone - Integrated 0.8W speaker - Integrated receiver - Class k audio amplifier
Camera	Integrated 13.0 MP rear camera
Keyboard & Input	5 buttons(1 user-definable key)
Network & Connectivity	- Intel® Wi-Fi 5 (802.11 ac) - Bluetooth® V5.0 - Integrated 4G LTE multi-carrier mobile broadband LTE-FDD(B1/2/3/4/5/7/8/13/17/20/28A/28B) LTE-TDD(B38/39/40/41) WCDMA(B1/2/5/8) GSM(B2/3/5/8) - Integrated GPS, Beidou and Glonass module

Security	Integrated HF-RFID (NFC) reader
Data Capture	1D/2D barcode reader
I/O Interface	- USB2.0(micro USB) x1 2 of 3 card slot (Nano Sim+Micro SD or Nano Sim+Nano Sim) 2pin POGOPin1 6pin POGOPin2 x1
Battery & Charging	- AC adapter: 100-240V, 50Hz-60Hz, 10W - Battery Li-Ion, 3.8V, 4500mAh, 16 hours
Environment	- Operating temperature: -10°C ~ 50°C (14°F ~ 122°F) - Storage tmperature: -20°C ~ 60°C (-4°F~140°F) - Humidity: 95% (Non-Condensing)
Dimension	162.4 mm(L) × 72.8 mm(W) × 19.4 mm(H)
Weight	250g
Accessories	- Standard: Adapter, Cable(typeC), Lanyard - Optional: Docking Charger, Vehicle Mount
Warranty	One-year limited warranty standard

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Optional



CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)
Tel: +86-(0)755-2372 2880 Email: marketing.info@emdoor.com
Web: www.emdoorrugged.com Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen