


10.4" Industrial Embedded Touch Panel PC

Model Number	Display & Touch Type				PC system			Fan (Yes/ No)	Storage		I/O Ports	Construction	Operating System	Optional Interfaces
	Size	Resolution	Viewing Angle (H-V)	Touch Type	CPU	Chipset	Graphic GPU		SSD	RAM				
NETPC410 J1900	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Celeron QuadCore J1900 , 2.0 GHz	Intel Bay trail	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 1 ; 2.0x 3) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 1 ; 2.0x 3) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 1 ; 2.0x 5) 6x RS232 COM(default)
NETPC410 i3-6006U	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Core i3-6006U (2.0GHz, dual core) (Gen 6th)	Intel Skylake	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 2 ; 2.0x 4) 6x RS232 COM(default)
NETPC410 i3-7020u	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Core i3-7020u (2.3GHz, dual core) (Gen 7th)	Intel Kabylake	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 2 ; 2.0x 4) 6x RS232 COM(default)
NETPC410 i5-6200U	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Core i5-6200U (2.3GHz, dual core) (Gen 6th)	Intel Skylake	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 2 ; 2.0x 4) 6x RS232 COM(default)
NETPC410 i5-7200U	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Core i5-7200U (2.5GHz, dual core) (Gen 7th)	Intel Kabylake	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 2 ; 2.0x 4) 6x RS232 COM(default)
NETPC410 i7-6500U	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Core i7-6500U (2.5GHz, dual core) (Gen 6th)	Intel Skylake	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 2 ; 2.0x 4) 6x RS232 COM(default)
NETPC410 i7-7500U	10.4"	1024*768	85/85/85/85	5-Wire Resistive Or 10-Finger- Multi Capacitive Touch	Intel® Core i7-7500U (2.7GHz, dual core) (Gen 7th)	Intel Kabylake	Intel® HD Graphics	No	64GB SSD	4G	1x VGA; 1x HDMI; MIC-In, EAR-Out 1x 12V DC-In	Silver Aluminum Bezel & Aluminum cooling shell and metal enclosure	(Default Pre-installed: Ubuntu) Support: Win7/8/10; Linux; 32Bit/64Bit	Option A: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 2x RS232 COM(default) Option B: Single LAN(1x1000Mbit RJ45 Ports) 4x USB (3.0x 2 ; 2.0x 2) 6x RS232 COM(default) Option C: Dual LAN(2x1000Mbit RJ45 Ports) 6x USB (3.0x 2 ; 2.0x 4) 6x RS232 COM(default)



Option A: One LAN+ 4x USB+ 2x RS232 COM



Bottom View



Top View

Option B: One LAN+ 4x USB+ 6x RS232 COM



Bottom View



Top View

Option C: Dual LAN+ 6x USB+ 6x RS232 COM



Bottom View



Top View

Configuration Options

Fan Option

Add fan in outer side

RAM/Memory Options

4GB

8GB MAX for J1900

16GB

Storage Options

64GB SSD

128GB SSD

256GB SSD

512GB SSD

HDD Storage Options

1T HDD(Hard Disk Drive)

2T HDD(Hard Disk Drive)

Expansion Options	
WiFi Expansion Kit – Kit includes antenna, WIFI includes bluetooth(two-in-one)	
2X RS232 COM Or 6X RS232 COM(Default)	
Choose 1x RS422 / 1xRS485 COM	
Included in the Delivery	
Power adapter;Short Installation Manual	